

ER8-6

Er Doped Single Clad Fiber

CorActive's Er-doped single clad fibers offer high QCE values, various doping concentrations, and different optical and geometrical characteristics to suit diverse customer requirements and applications. CorActive's ER8-6 Er-doped single clad fiber features high absorption and high quantum efficiency that make this product the ideal solution for the design of optical telecom amplifiers.

SPECIFICATIONS

Optical

Core Absorption @ 1530nm	dB/m	8 ± 1
Core Absorption @ 980nm	dB/m	≥ 6.0
Nominal Core NA		0.22
Cutoff Wavelength	nm	900 ± 50
Mode Field Diameter	μm	6.5 ± 0.5

Geometrical&Mechanical

Clad Diameter	μm	125 ± 0.5
Coating Diameter	μm	245 ± 10
Proof Test	kpsi	≥ 150

TYPICAL APPLICATIONS

- Optical Amplifiers
- PON Networks
- CATV/Telecom Applications

ADVANTAGES

- Low background losses
- High quantum conversion efficiency lowers pump power requirements, reducing overall system costs

RELATED PRODUCTS

- Higher absorption version: ER12-6

CorActive High-Tech, Inc.
2700 Jean-Perrin, Suite 121, Quebec City, QC
Canada G2C 1S9
Phone : 1-866-845-2466
E-mail : sales@coractive.com
www.coractive.com

CorActive
Specialty Optical Fiber Manufacturer