

Polarization Scrambler

PS3000 Series

FIBERPRO's Polarization Scramblers perform polarization scrambling at high speed and make Degree Of Polarization (DOP) zero on time average. It is based on all fiber technology that has enabled us to build very low insertion loss, back reflection free and a compact polarization scrambler.

Polarization dependence is one of the biggest issues in fiber-optic measurement, communications and sensors. PDL in components and equipments, Polarization Dependent Gain (PDG) in EDFA are typical examples.

Depolarizing is one of the solutions for the polarizing problems. Polarization Scrambler provides the best solution for most situations in which the depolarization is needed.

This equipment provides you with an excellent way to characterize / qualify optical property of optical devices. Furthermore, our PS can solve the problems associated with PDG of EDFAs by scrambling polarization of the optical signal.



Features

- High speed scrambling (~1MHz)
- All single mode fiber configuration (Low loss, Low PMD)
- Wide operating wavelength range
- Input polarization independent
- GPIB, RS232, USB remote interface.
- Plug & Play

Specifications

| Model | PS3010 | PS3210 |
|-------------------------------------|---|--------|
| Output DOP | < 5% | |
| Polarization Modulation Frequencies | ~ 1MHz ¹⁾ | |
| Center Wavelength | 1310nm | 1310nm |
| | 1480nm | 1550nm |
| | 1550nm | 1570nm |
| | 1590nm | |
| Operating Wavelength Range | > 40nm | > 80nm |
| Insertion Loss | < 1.0dB (with connectors) | |
| Average PMD | < 0.3 ps | |
| PDL | < 0.05dB (with connectors) | |
| Return Loss | > 40dB (PC connector) | |
| | > 60dB (APC connector) | |
| Operating Temperature Range | 5°C ~ 35°C ²⁾ (DOP < 5%) | |
| Input / Output Connectorization | FC / PC ³⁾ (standard) | |
| Interface | GPIOB / RS232 / USB | |
| Power Input | 100 ~ 250V, 50Hz / 60Hz free voltage | |
| Dimensions (W x D x H) | 234mm x 410mm x 108mm (With rubber cover) | |
| | 212mm x 380mm x 86mm (Without rubber cover) | |

1) It is fine-tuned for optimum operation at the factory.

2) In the range of 0°C ~ 50°C, the output DOP slightly increases, however it is less than 10%.

3) Other connectorization is available. Specify when you order.

Ordering Codes

PS(1) - (2) - (3)

1. Model No. ➡ 3010 / 3210

2. Center wavelength

PS3010 ➡ 131 : 1310nm

148 : 1480nm

155 : 1550nm

159 : 1590nm

PS3210 ➡ 131: 1310nm

155 : 1550nm

157 : 1570nm

3. Connector type ➡ F / P : FC / PC

F / A : FC / APC

S / P : SC / PC

S / A : SC / APC



日本デバイス株式会社 E-mail sales@j-device.com

www.j-device.com

Tel 03-6262-3424 Fax 03-6800-5883



FIBERPRO Headquarters

FIBERPRO USA

FIBERPRO CHINA

www.fiberpro.com

Tel : +82-42-360-0030

Tel : +1-408-835-7796

Tel : +86-27-8663-5497

sales@fiberpro.com

Fax : +82-42-360-0050

Fax : +1-408-521-0402

Fax : +86-27-8663-5701