

Industrial confidentiality

PRODUCT SPECIFICATION

Product code:

IXF-RAD-AMP-2-PM

	Parameter	Specification	Units
1	Absorption @ 1530 nm	24.5 ±3	dB/m
2	Absorption @ 980 nm	16.5 ±3	dB/m
3	MFD @ 1550 nm	5.5 ±1	μm
4	Background losses	< 20	dB/km
5	Cutoff Wavelength	< 1200	nm
6	Cladding Diameter	125 ±2	μm
7	Coating Diameter	245 ±10	μm
8	Proof test level	100	kpsi
9	Splice Loss (to PM1550)	< 0.20	dB
10	RIA @1545nm	< 0.015	dB/m/kRad
11	RIA @980nm	< 0.025	dB/m/kRad
12	Birefringence	>2.10 ⁻⁴	

Comments

RIA: Radiation Induced Attenuation

Effective date of this document: 23/09/2024

Edition: F

Document reference: IXF-RAD-AMP-2-PM_edE.pdf

Specifications are subject to change without notice

PSD-L-Q-E-086-I



ixblue S.A.S.
ixblue Photonics – Specialty Fibers Division
Rue Paul Sabatier, 22300 Lannion, France

T. : +33 1 30 08 94 50
www.photonics.ixblue.com

Société par Actions Simplifiée au capital de 11 442 897 €
R.C.S. Versailles 433 185 121 - SIRET 433 185 121 00061
Code APE 2651B - N° TVA Intra. FR 09 433 185 121



日本デバイス株式会社 E-mail sales@j-device.com

www.j-device.com

Tel 03-6262-3424 Fax 03-6800-5883